

Reducing the use of Storm Overflows

Dr Nick Mills

Head of the Clean Rivers & Seas Task Force



from
**Southern
Water** 


The Clean Rivers & Seas Task Force

The **Clean Rivers and Seas Task Force** was set up in 2021, **our aim is to reduce storm overflows** to ensure a healthy environment and water resilient future.

The task force is responsible for **delivering pathfinder projects** through an **accelerated programme** to reduce the use of storm overflows over the next two years. We're collaborating across industries as well as with local authorities and the public.

We've **built our Clean Rivers and Seas (regional) plan**. This is hosted on a public interactive map to show how the company will reduce storm overflow releases, in line with regulatory and government targets.

Find out more - [Storm Overflows \(southernwater.co.uk\)](https://southernwater.co.uk)




We have taken a holistic and sustainable approach

There are four main ways to reduce the use of storm overflows



Source control: removing or 'slowing the flow' of water entering the sewer system to prevent it from becoming overwhelmed and needing to use storm overflows. For example, using sustainable drainage systems (SuDS).



Infrastructure optimisation: using smart controls on our network, storage tanks and pumps, unlocking extra storage, and going beyond permits to make sure we use our infrastructure to its full potential.




Stormwater treatment: a new and innovative step in the process, we're using wetlands to clean and pre-treat stormwater before it is released to the environment.




Building bigger infrastructure: sometimes new or bigger infrastructure like storm tanks is necessary, but we see this as a last resort, after exhausting all source control, infrastructure improvement and nature-based options.

We used AI and enhanced analysis to understand the dominate cause for storm overflow activation, so we could target the right approach and solutions.




**Total storm overflow releases: 19,807
by reason for release**




The main sources of excess water in surface water catchments are roads and roofs

Source of Inflow of a 1 in 20 year Storm Event (2020)



We must target interventions with detailed insight of the catchment and requires investigation of drainage assets much of which we don't own.



Step 1: Optimisation

Reconfiguring our permits and existing sites to help us reduce storm overflows




from Southern Water.

Pathfinder Process: Surface water

1. Optimising infrastructure
2. Misconnections
3. Household SuDS
4. Non-Household SuDS
5. Highway Schemes



CASE STUDY Optimising infrastructure to slow the flow in Whitstable



Swalecliffe WTW, Kent
Storm tank reconfiguration

Step 2: Misconnections

Redirecting surface water that has been misconnected into the foul/combined sewer

Pathfinder Process: Surface water

1. Optimising infrastructure
- 2. Misconnections**
3. Household SuDS
4. Non-Household SuDS
5. Highway Schemes



Gurnard, Isle of Wight
Large surface water misconnection



**WATER
for LIFE**

from
Southern
Water.

Step 3: Household SuDS

Rolling out 'slow the flow' measures at scale on properties in our catchments

Pathfinder Process: Surface water

1. Optimising infrastructure
2. Misconnections
- 3. Household SuDS**
4. Non-Household SuDS
5. Highway Schemes

CASE STUDY

Using slow-drain water butts
slow the flow in
Havenstreet



Step 4: Non-Household SuDS

Targeting large roof areas with 'slow the flow' measures to deliver impact

Pathfinder Process: Surface water

1. Optimising infrastructure
2. Misconnections
3. Household SuDS
- 4. Non-Household SuDS**
5. Highway Schemes

CASE STUDY Sustainable Drainage Systems (SuDS) to **slow** **the flow in schools**

Map shows roofs over 300m² in red



Gurnard, Isle of Wight
'Slow the flow' planters installed at a care home

Step 5: Highway SuDS Schemes

With significant volumes of surface water coming from public highways, influencing the design of placemaking schemes will be an essential part of the solution

Pathfinder Process: Surface water
1. Optimising infrastructure
2. Misconnections
3. Household SuDS
4. Non-Household SuDS
5. Highway Schemes

Sustainable drainage systems (SuDS) are an eco-friendly and sustainable way to create better drainage of rainwater and groundwater in communities.




Cornwallis Circle, Whitstable
Managing 1.2 hectares of impermeable area with regreening; featuring swales and tree planting



Newport High Street, Isle of Wight
Plans for highway SuDS

The results


Our results to date show a measurable spills reduction




The results

The comparison with an end of pipe solution


Storm tank storage doubled at Lyndhurst with 4 x 75m³ nurse tanks



We used AI and enhanced analysis to understand the dominate cause for storm overflow activation, so we could target the right approach and solutions.





**Total storm overflow releases: 19,807
by reason for release**





In low groundwater conditions

pumping stations convey the foul flow and a small amount of infiltration to the wastewater treatment works.




In high groundwater conditions

the flow is largely infiltration. At these levels the pumps are working continuously and tankers are required to keep the sewerage system functioning.




In extreme groundwater conditions

infiltration gets into the network through all pipes and inundates the pumping stations. Overpumping arrangements with UV treatment are used to prevent property flooding.



*on a wastewater treatment works a storm overflow will activate.



In areas of acute ground water we will optimise, seal private and public sewers to limit the ground water ingress and...

Pan-Parish near Andover, Hampshire



Seal everything
Public sewers
Public manholes
Private drains

Seal public defects
Seal leaks from electroscans
Seal MHs between sealed pipes
Scan the rest of the public network

Investigate condition of
public sewers
Scan all the pipes



Tube-gel technology being used to seal private pipes

... build wetland treatment for excess water from each overflow



Lavant near Chichester, West Sussex




from Southern Water.

Our plans



Our AMP8 (2025-2030) environmental plan is very large.




Our AMP8 (2025-2030) plan includes multiple environmental improvements in the new Forest.



- Southern Water Boundary
 - ✱ Key Site
 - Surface Water Catchment
 - Waterbody Sub-Catchments
 - River, Canal and Surface Water Bodies
 - MCERTS Proposed Monitoring
 - High Quality Drinking Water from Sustainable Sources
 - ◆ Storm Overflow
 - Improving sea and river water quality
 - Sludge Recycling and Sustainability
- Bathing Water Condition**
- Excellent
 - Good
 - Sufficient
 - Poor
- Environmental Designations**
- Site of Special Scientific Interest (SSSI)
 - Special Protection Area (SPA)
 - Special Area of Conservation (SAC)
 - Ramsar
 - Area of Outstanding Natural Beauty (AONB)
 - Marine Conservation Zones

Storm overflow improvements have a multi-AMP programme



Our planned investments in the New Forest

Site	Driver	Details	Cost estimate (£m)
Lyndhurst WTW	Nutrients	Total Nitrogen Permit (10mg\ltr - TAL)	10.2
	Storm Overflows	Groundwater – public and private network sealing and wetland treatment (2035)	1.5
Brockenhurst WTW	Nutrients	Total Nitrogen Permit (10mg\ltr - TAL) (2035)	7.7
	Nutrients	Treatment for Phosphorus removal (chemical)	2.0
	Storm Overflows	Groundwater – public and private network sealing and wetland treatment	2.3
Beaulieu WTW	Storm Overflows	Surface Water management of non-permeable area with SuDS	1.5
Ashlett Creek WTW	Nutrients	Total Nitrogen Permit (10mg\ltr - TAL)	22.0
	Storm Overflows	Combination of groundwater and surface water management interventions	0.7
Pennington WTW	Growth	Increase capacity of site for forecast growth in the catchment	19.0
	Storm Overflows	Groundwater – public and private network sealing and wetland treatment	9.9
Slow Hill Copse WTW	Nutrients	Total Nitrogen Permit (10mg\ltr - TAL)	19.8
	Storm Overflows	Surface Water management of non-permeable area with SuDS	13.5
Total Estimated Cost (£m)			110.0

TAL – Technological Achievable Limit, SuDS – Sustainable Drainage Systems

Thank you

Dr Nick Mills

